

Lubrimax® Alu Quick

acc. to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.0 Date of compilation: 2022-10-14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: <u>Lubrimax® Alu Quick</u>
Unique formula identifier (UFI) G8J0-W0GU-900P-SQRR

Alternative number(s) 9761632

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Lubricant

Industrial uses: uses of substances as such or in preparations at industrial site

Uses advised against Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Steidle GmbH

D-51371 Leverkusen, Röttgerweg 12, Germany T: +49 (0) 214 / 82511 - 25 info@steidle-gmbh.de F: +49 (0) 214 / 82511 - 26 www.steidle-gmbh.de

Informing: Dept. Technic T: +49 (0) 214 / 82511 – 22

1.4 Emergency telephone number: see above or consult the next poison information department

Code: 9761632

UFI: G8J0-W0GU-900P-SQRR

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.10	aspiration hazard	1	Asp. Tox. 1	H304
4.1C	hazardous to the aquatic environment - chronic hazard	4	Aquatic Chronic 4	H413

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word danger

Pictograms



GHS08

Hazard statements

H304 May be fatal if swallowed and enters airways.
H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazardous ingredients for labelling

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics, Hydrocarbons, C11-C12, isoalkanes, <2% aromatics, 2,2,4,6,6-pentamethylheptane

2.3 Other hazards

This material is combustible, but will not ignite readily.

TECH163-GB-Rev13.doc – 12.22 page: 1 of 8



Lubrimax® Alu Quick

acc. to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.0 Date of compilation: 2022-10-14

2.3.2 Ergebnisse der PBT- und vPvB-Beurteilung

Dieses Gemisch enthält keine Stoffe, die als PBT- oder vPvB-Stoff beurteilt werden.

* SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Hydrocarbons, C10-C13, n-alkanes,	CAS No 64771-72-8	50-<75	Asp. Tox. 1 / H304
<2% aromatics	EC No 929-018-5		EUH066
	REACH Reg. No 01-2119475608-26-xxxx		
Hydrocarbons, C11-C12,	CAS No 90622-57-4	25-<50	Flam. Liq. 3 / H226
isoalkanes, <2% aromatics	EC No 918-167-1		Asp. Tox. 1 / H304
	REACH Reg. No 01-2119472146-39-xxx		Aquatic Chronic 4 / H413
			EUH066
2,2,4,6,6-pentamethylheptane	CAS No 13475-82-6	5-<10	Flam. Liq. 3 / H226
	EC No 236-757-0		Asp. Tox. 1 / H304
	REACH Reg. No 01-2119490725-29-xxxx		Aquatic Chronic 4 / H413
	-		EUH066

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contac

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delaye

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Water spray, BC-powder, Carbon dioxide (CO2) Unsuitable extinguishing media Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

TECH163-GB-Rev13.doc – 12.22 page: 2 of 8



acc. to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.0 Date of compilation: 2022-10-14

Lubrimax® Alu Quick

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gase.

6.2 Environmental precautions:

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up:

Advice on how to contain a spill Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and release

Place in appropriate containers for disposal. Ventilate affected area

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation.

Use local and general ventilation. Use only in well-ventilated area.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupatio	Occupational exposure limit values (Workplace Exposure Limits)										
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling- C [ppm]	Ceiling- C [mg/m³]	Notation	Source
GB	2,2,4,6,6- pentamethylheptane		WEL		1,200					proc	
GB	2,2,4,6,6- pentamethylheptane		WEL		800					proc	
GB	aromatics		WEL		500					proc	EH40/2005

Notation

(> or = C7, Normal and branched chain alkanes)

Ceiling-C ceiling value is a limit value above which exposure should not occur

proc substances released during the process

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified)

TECH163-GB-Rev13.doc – 12.22 page: 3 of 8



acc. to Regulation (EC) No. 1907/2006 (REACH)

Lubrimax® Alu Quick

Date of compilation: 2022-10-14

8.2 Exposure controls

Version number: GHS 1.0

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leaktightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Type of material

Nitrile

Material thickness

> 1 mm.

Breakthrough times of the glove material

>60 minutes (permeation: level 3)

Not suitable are gloves made of the following material:

Fabric, Leather

Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless - transparent
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	not determined
Flash point	≥62 °C (o.c.)
Auto-ignition temperature	not determined
Decomposition temperature	not relevant
pH (value)	not applicable
Kinematic viscosity	2.2 – 2.8 mm ² /s at 20 °C 1.5 – 1.9 mm ² /s at 40 °C
Water solubility	insoluble

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available		
Vapour pressure	not determined		

Density and/or relative density

Density	0.75 – 0.77 g/cm³ at 20 °C		
Relative vapour density	information on this property is not available		
Particle characteristics	not relevant (liquid)		

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant		
Other safety characteristics	there is no additional information		

TECH163-GB-Rev13.doc – 12.22 page: 4 of 8



Lubrimax® Alu Quick

acc. to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.0 Date of compilation: 2022-10-14

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions:

No known hazardous reactions.

10.4 Conditions to avoid:

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials:

Oxidisers

10.6 Hazardous decomposition products:

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitise.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Other information

Repeated exposure may cause skin dryness or cracking.

11. Information on other hazard

There is no additional information.

TECH163-GB-Rev13.doc – 12.22 page: 5 of 8



Lubrimax® Alu Quick

page: 6 of 8

acc. to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.0 Date of compilation: 2022-10-14

SECTION 12: Ecological information

12.1 Toxicity

May cause long lasting harmful effects to aquatic life.

12.2 Persistence and degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradationrate	Time	Method	Source
Hydrocarbons,	64771-72-8	oxygen depletion	77 – 83 %	28d		
C10-C13, n-alkanes, <2% aromatics						
Kohlenwasserstoffe, C11-C12,	90622-57-4	oxygen depletion	31 %	28 d		
Isoalkane, < 2% Aromaten						

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13 Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilitie.

SECTION 14: Transport information

14.1 UN number or ID numbe

not subject to transport regulation

14.2 UN proper shipping name

not relevan

14.3 Transport hazard class(es)

none

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.



Lubrimax® Alu Quick

acc. to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.0 Date of compilation: 2022-10-14

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/UE (Se	2012/18/UE (Seveso III)					
Nr.	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes			
	not assigned					

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed.

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed.

National regulations (GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate lis none of the ingredients are listed

Restrictions according to GB REACH, Annex 17

none of the ingredients are listed

Dangerous substances with restrictions (GB REACH, Annex 17)				
Name of substance Name acc. to inventory		CAS No	No	
Lubrimax® Alu Quick	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3	

Toxic Substance Control Act (TSCA)

all ingredients are listed

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

TECH163-GB-Rev13.doc – 12.22 page: 7 of 8



acc. to Regulation (EC) No. 1907/2006 (REACH)

Lubrimax® Alu Quick

Version number: GHS 1.0 Date of compilation: 2022-10-14

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
Flam. Liq.	Flammable liquid
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the Inter-
OTEL	national carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula)

List of relevant phrases (code and full text as stated in section 2 and 3)

LIST OF TOTAL	vant privages (code and run text as stated in section 2 and 3)
Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

TECH163-GB-Rev13.doc – 12.22 page: 8 of 8